



Dimensions

Size mm	8	10	15	20	25	32	40	50	65	80	100
L	•	•	70	72	80	117	120	141	182	205	285
H	•	•	44	51	54	72	82	86	120	126	160
D	•	•	•	•	•	•	•	•	•	•	•
Wt/kgs	•	•	0.35	0.5	0.8	2.0	2.1	2.8	6.5	8.0	19.5

■ **Pressures:** 2100 kPa CWP
Steam: 1200 kPa @ 200°C

■ **Standards:** Dezincification Resistant
AS 1628 – 1994: Copper Alloy Valves
AS 3855: Materials suitable for Potable Water Service

ITEM	DESCRIPTION	MAT'L	STANDARD
7	SPINDLE NUT	DR BRASS	AS1567-352
6	SPINDLE – PIN	STAINLESS STEEL	ASTM A276 94A AISI316
5	DISC NUT	DR BRASS	AS1567-352
4	DISC – FLAP (A)	GUNMETAL BRONZE	AS1565 C83600M
3	ARM (A)	GUNMETAL BRONZE	AS1565 C83600M
2	CAP – BONNET	GUNMETAL BRONZE	AS1565 C83600M
1	BODY	GUNMETAL BRONZE	AS1565 C83600M



PROMET VALVES AUSTRALIA
1A Green Road Woodville West SA 5011
www.prometvalves.com promet@prometvalves.com
T: 08 8268 1777 ABN 47096 425 697 F: 08 8268 1711

FIG No

T4B

BRONZE SWING CHECK

VALVE SCREWED

CLASS 21
PN 20