



Z60M

CAST BRONZE GATE VALVE

INSIDE SCREW - NON RISING STEM - BRONZE TRIM

An AS 2129 Table E Cast Bronze Wedge Gate Valve with a Screwed Cover. Non Rising Stem, Inside Screw with Bronze Trim.

PRESSURE/TEMPERATURE RATING

Max Service Temp 170°C (338°F).
Water, Oil or Gas up to 1400KPA (200PSI)

OPTIONS

Open and shut indicator.
Locked bonnet.
Valves manufactured in other flange and body material specifications on request.

DIMENSIONS - mm

Size	25	32	40	50	65	80	100
A	89	95	102	114	121	140	178
B	115	130	150	180	230	260	320
Mass kg	2.4	2.7	4	5.4	8.1	11.5	20.4

MATERIAL SPECIFICATIONS

No.	Component	Material	AS or BS Specification
1	Handwheel Nut	Stainless Steel	-
2	Handwheel	Cast Iron	-
3	Gland Nut	DR. Brass	AS 1567-486
4	Gland Follower	DR. Brass	AS 1567-486
5	Packing	PTFE	-
6	Stuffing Box	DR. Brass	AS 1567-486
7	Spindle	DR. Brass	AS 1567-486
8	Cover	Cast Bronze LG2	AS 1565-C83600
9	Body	Cast Bronze LG2	AS 1565-C83600
10	Wedge	Cast Bronze LG2	AS 1565-C83600

