

Cast Iron Flanged 'Y' Strainer Table E




Material List	
PART	MATERIAL
Body	Cast Iron (epoxy coated)
Screen	304 Stainless Steel
Gasket	Graphite
Cover	Cast Iron
Plug	Malleable Iron

Applications - Water, Oil, Air

Specifications	
Flange	AS2129 T/E
Max Working Temperature	120°C
Cold Working Pressure	1600kPa

Effective Open Area		
Size	Screen Openings	(% of Inlet Pipe)
50mm - 150mm	1.5mm diam @ 4.5mm spacing	33%
200mm - 300mm	3mm diam @ 7.5mm spacing	44%



Cast Iron Flanged 'Y' Strainer Table E						
CODE	IMPERIAL SIZE	L	H	HOLE DIAMETER	NO. HOLES	APPROX. KG/PC
VDIY50	2	225.4	144	18	4	10
VDIY65	2 1/2	273	176	18	4	14
VDIY80	3	292.1	195	18	4	19
VDIY94	4	352.4	246	18	8	33
VDIY95	5	416	300	18	8	50
VDIY96	6	470	320	22	8	55
VDIY98	8	543	397	22	8	99
VDIYX25	10	660.4	483	22	12	169
VDIYX30	12	762	560	26	12	245
VDIYX35	14	950	689	26	12	450