



15A 20A DESIGN: BALL TYPE

25A DESIGN: PTFE DISC TYPE

**Options:** Lever can be removed use with FA222 organ whistle

■ **Pressures:** 1000 kPa

■ **Services:** Water • Oil • Gases • Air  
Steam temp to 180°C

**Dimensions**

Size mm	15	20	25				
L	58	65	102				
H	51	51	70				
B	32	32	48				
A	120	130	135				
Wt/kgs	0.45	0.55	1.25				

11	STEM – PISTON	STAINLESS STEEL	ASTMA276 AISI316
10	BALL DISC	STAINLESS STEEL	AISI302
9	SPINDLE	DR BRASS	AISI567 -352
8	PIN CLEVIS	STEEL	
7	GLAND PACKING	PTFE GPI BUSH	AS1198
6	ARM-LEVER	GUNMETAL BRONZE	AS1565 C83600(m)
5	SPRING	STAINLESS STEEL	JIS4313 GR304
4	GLAND FOLLOWER	DR BRASS	AISI567 -352
3	VALVE – DISC PTFE	DR BRASS	AISI567 -352
2	END CAP	DR BRASS	AISI567 -352
1	BODY	GUNMETAL BRONZE	AS1565 C83600(m)
ITEM	DESCRIPTION	MAT'L	STANDARD



**PROMET VALVES AUSTRALIA**

1A Green Road Woodville West SA 5011  
www.prometvalves.com promet@prometvalves.com  
T: 08 8268 1777 ABN 47096 425 697 F: 08 8268 1711

FIG No  
**FA240**

**BRONZE 'WHISTLE'  
RELIEF VALVE**